



Capacity: 30 litres

Internal measures: 550 x 300 x 250 mm.

Basket measures: 530 x 284 x 85 mm.

Useful measures: 500 x 260 x 175 mm.

External measures: 720 x 410 x 490 mm.

Weight: 34 kg

ELECTRICAL CHARACTERISTICS:

- Power Supply: 220V.
- Heating element: 1000 W.

ULTRASONIC CHARACTERISTICS:

- Ultrasonic Power: 600W (1200W p-p).
- 1 ultrasonic generator with 600W (1200W p-p) output power.
- Working frequency: 40 KHz sweep system \pm 2%.
- 12 high-performance IBL piezo-electric transducers in titanium-steel.

CONTROL PANEL:

- General switch.
- DEGAS system to degas the water.
- Ultrasounds timer.
- Temperature selector.
- Power level selector: 50%-100%.

FINISHING AND ACCESSORIES:

- Tank built in AISI 316 Stainless steel, 2 mm thick.
- External panel in fingerprint-resistant steel, 1 mm thick.
- Thermo-acoustic isolator K-Flex Duct Net, 20 mm thick.
- Integrated handles on the external panel.
- Stainless steel basket with anchorage system for loading, unloading and draining pieces.
- ½" draining ball valve.
- Insulated tank cover in Stainless-Steel with pneumatic shock absorber.